


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 106.47 lm/W			
MODEL: ST2WDE-01-US-HR-HQ-HE		Imax(cd)	439.8	S/MH(C0/180)	1.41
NOMINAL POWER(W)	12.0272	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	AC 120	TOTAL FLUX(lm)	1291.9	□ UP,DN(C0-180)	2.8,46.6
NOMINAL FLUX(lm)	1291.9	CIE CLASS	DIRECT	□ UP,DN(C180-360)	2.7,48.0
LAMPS INSIDE	1	□ up(%)	5.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	AC 120	□ down(%)	94.6	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-12-29

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 4.880m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	400.4	408.6	422.2	432.7	438.6	430.8	419.6	407.8	0- 10	40.45	40.45	3.13,3.13
20	356.5	376.4	405.3	424.6	435.6	422.5	401.2	374.5	10- 20	116.2	156.7	12.1,12.1
30	307.9	329.4	375.9	404.0	412.7	400.3	371.6	325.1	20- 30	177.1	333.8	25.8,25.8
40	251.2	275.6	331.4	360.9	363.9	358.2	326.8	268.6	30- 40	214.7	548.6	42.5,42.5
50	213.4	216.4	268.0	291.4	298.4	292.6	261.8	214.1	40- 50	222.7	771.2	59.7,59.7
60	109.0	151.3	184.6	212.4	238.7	217.0	179.0	138.8	50- 60	195.9	967.2	74.9,74.9
70	62.83	70.59	98.05	133.4	165.4	138.4	96.34	64.94	60- 70	137.9	1105	85.5,85.5
80	34.14	32.85	33.64	67.25	98.10	72.65	33.33	29.92	70- 80	79.85	1185	91.7,91.7
90	18.71	18.94	2.008	26.96	46.81	31.05	2.138	15.80	80- 90	36.58	1222	94.6,94.6
100	15.51	14.88	1.486	14.22	20.79	15.00	1.569	11.30	90-100	17.01	1239	95.9,95.9
110	17.05	13.07	1.955	11.72	13.21	11.68	2.100	12.83	100-110	11.51	1250	96.8,96.8
120	25.13	11.95	2.485	11.02	12.04	10.79	2.635	11.45	110-120	10.11	1260	97.5,97.5
130	35.19	12.42	3.002	12.38	13.59	11.54	3.133	9.862	120-130	10.18	1270	98.3,98.3
140	31.25	5.808	3.482	14.29	23.52	14.61	3.598	3.810	130-140	9.931	1280	99.1,99.1
150	5.809	4.112	3.962	10.02	22.22	13.27	4.039	4.171	140-150	6.551	1287	99.6,99.6
160	4.535	4.474	4.373	5.399	13.34	5.731	4.424	4.518	150-160	3.180	1290	99.9,99.9
170	4.805	4.760	4.703	4.603	4.552	4.631	4.729	4.790	160-170	1.445	1291	100,100
180	4.894	4.884	4.891	4.880	4.891	4.887	4.886	4.885	170-180	0.4559	1292	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 660.77 lm

%lum = 51.1%

%lamp = 51.1%

Conical surface Flux(120deg): 967.16 lm

%lum = 74.9%


%lamp = 74.9%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-12-29

□ Range: 0 - 180DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	35023	18643
80	24577	24214
75	23315	30011
70	22963	35833
65	23273	41317
60	27258	46139
55	35619	49689
50	41493	52122
45	42155	53458

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 4.880m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0	
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
□fc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.313	.178	.056	.305	.174	.055	.288	.165	.053	.273	.158	.051	.259	.150	.048		
2.0	.290	.159	.049	.282	.156	.048	.268	.149	.046	.255	.143	.045	.242	.137	.043		
3.0	.267	.142	.043	.260	.139	.042	.247	.134	.041	.235	.129	.040	.224	.124	.038		
4.0	.246	.128	.038	.240	.126	.037	.229	.121	.036	.218	.117	.035	.208	.113	.034		
5.0	.228	.116	.034	.222	.114	.033	.212	.110	.032	.202	.107	.032	.193	.103	.031		
6.0	.211	.106	.030	.206	.104	.030	.197	.101	.029	.188	.098	.029	.180	.095	.028		
7.0	.197	.097	.028	.192	.096	.027	.184	.093	.027	.176	.090	.026	.168	.087	.026		
8.0	.184	.090	.025	.180	.088	.025	.172	.086	.025	.165	.083	.024	.158	.081	.024		
9.0	.172	.083	.023	.169	.082	.023	.162	.080	.023	.155	.078	.022	.149	.076	.022		
10.0	.162	.078	.022	.159	.077	.021	.152	.075	.021	.146	.073	.021	.140	.071	.020		

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.232	.232	.232	.198	.198	.198	.135	.135	.135	.078	.078	.078	.025	.025	.025	
1.0	.222	.198	.176	.190	.170	.151	.130	.117	.105	.075	.068	.061	.024	.022	.020	
2.0	.214	.174	.140	.183	.150	.121	.126	.104	.085	.072	.060	.050	.023	.020	.016	
3.0	.206	.157	.117	.177	.135	.101	.121	.094	.071	.070	.055	.042	.023	.018	.014	
4.0	.199	.143	.101	.171	.124	.088	.117	.086	.062	.068	.051	.037	.022	.016	.012	
5.0	.191	.133	.090	.164	.115	.079	.113	.080	.055	.066	.047	.033	.021	.015	.011	
6.0	.184	.125	.082	.158	.108	.072	.109	.076	.051	.063	.045	.030	.020	.015	.010	
7.0	.178	.118	.076	.153	.102	.067	.106	.072	.047	.061	.042	.028	.020	.014	.009	
8.0	.171	.112	.072	.147	.097	.063	.102	.068	.045	.059	.040	.027	.019	.013	.009	
9.0	.165	.107	.068	.142	.093	.060	.099	.066	.042	.057	.039	.025	.019	.013	.008	
10.0	.160	.103	.066	.138	.090	.057	.095	.063	.041	.056	.037	.024	.018	.012	.008	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: LED Strip					TYPE: Indoor lighting					WEIGHT: 20				
SPEC.: 高压灯带					DIM.: 1000*12*8					SERIAL No.: 20201229002				
MFR.: EVERFINE					SUR.: 1000*12*8cm					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					23.1	24.6	23.5	24.9	25.2	24.6	26.0	24.9	26.3	26.6
3H					23.9	25.2	24.3	25.6	25.9	25.8	27.1	26.2	27.4	27.8
4H					24.4	25.6	24.7	26.0	26.3	26.2	27.4	26.6	27.8	28.2
6H					24.8	26.0	25.2	26.3	26.7	26.4	27.6	26.8	28.0	28.4
8H					25.0	26.1	25.4	26.5	26.9	26.5	27.6	26.9	28.0	28.4
12H					25.2	26.3	25.6	26.7	27.1	26.5	27.6	26.9	28.0	28.4
4H 2H					23.7	24.9	24.1	25.3	25.6	24.8	26.1	25.2	26.4	26.8
3H					24.6	25.7	25.0	26.1	26.5	26.2	27.3	26.6	27.7	28.1
4H					25.2	26.2	25.6	26.6	27.0	26.7	27.7	27.1	28.1	28.6
6H					25.8	26.6	26.2	27.1	27.6	27.0	27.9	27.5	28.4	28.9
8H					26.0	26.9	26.5	27.3	27.8	27.1	28.0	27.6	28.4	28.9
12H					26.4	27.1	26.9	27.6	28.1	27.2	28.0	27.7	28.4	29.0
8H 4H					25.4	26.2	25.9	26.7	27.2	26.8	27.6	27.3	28.0	28.5
6H					26.1	26.8	26.7	27.3	27.9	27.2	27.9	27.8	28.4	29.0
8H					26.6	27.2	27.1	27.7	28.3	27.4	28.0	27.9	28.5	29.1
12H					27.1	27.6	27.6	28.1	28.7	27.5	28.1	28.1	28.6	29.2
12H 4H					25.4	26.1	25.9	26.6	27.1	26.7	27.5	27.3	28.0	28.5
6H					26.2	26.8	26.8	27.3	27.9	27.3	27.9	27.8	28.4	29.0
8H					26.7	27.2	27.3	27.8	28.4	27.5	28.0	28.1	28.6	29.1
Variations with the observer position at spacings(CIE Pub.117):														
S = 1.0H					+ 0.2 / - 0.2					+ 0.1 / - 0.2				
1.5H					+ 0.4 / - 0.6					+ 0.2 / - 0.3				
2.0H					+ 0.5 / - 0.8					+ 0.5 / - 0.5				

CIE Pub.117, 1292 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.9)
Area: 0.008 m2


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

AAI Figure

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2020-12-29

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270
0	428	429	426	426	426	426	426	426	427	427	429	429	428	429	426	426	426	426	426
5	417	418	418	419	421	424	425	427	429	432	434	436	436	435	432	430	429	427	424
10	400	404	405	409	413	417	422	425	430	433	436	438	439	436	434	431	427	424	420
15	380	385	388	394	401	409	415	421	426	430	434	436	439	436	432	428	424	418	412
20	356	362	368	376	386	396	405	413	419	425	430	433	436	431	427	423	416	410	401
25	329	336	343	355	367	381	393	403	410	416	422	425	426	423	418	412	407	399	389
30	308	311	317	329	345	362	376	388	396	404	408	411	413	409	405	400	394	384	372
35	282	289	292	303	319	339	356	369	379	385	388	390	391	388	385	382	376	365	351
40	251	258	266	276	290	313	331	347	356	361	360	361	364	361	360	358	354	342	327
45	238	242	240	245	259	281	302	318	327	329	326	327	331	327	328	329	326	315	296
50	213	219	222	216	225	246	268	285	292	291	289	292	298	294	293	293	292	281	262
55	163	176	186	191	190	208	228	245	249	251	254	261	268	262	258	255	253	241	222
60	109	118	135	151	157	168	185	201	206	212	221	231	239	232	225	217	210	199	179
65	78.7	83.1	91.4	106	118	129	140	155	163	174	184	192	200	193	186	177	167	154	136
70	62.8	65.0	65.6	70.6	79.8	91.0	98.0	111	121	133	146	158	165	159	152	138	126	112	96.3
75	48.3	49.9	49.1	48.0	50.5	57.4	62.1	73.8	84.3	97.8	110	123	132	126	117	104	89.7	75.0	61.3
80	34.1	35.5	35.3	32.9	30.8	32.0	33.6	44.6	54.7	67.3	77.8	89.1	98.1	92.2	84.5	72.7	59.6	45.9	33.3
85	24.4	25.2	25.4	23.9	19.2	15.0	13.0	24.3	33.8	43.0	52.7	62.1	69.2	64.7	58.4	48.5	37.6	25.1	13.1
90	18.7	19.2	19.5	18.9	14.9	7.79	2.01	11.6	20.5	27.0	33.4	41.4	46.8	43.2	37.9	31.1	23.0	12.1	2.14
95	16.4	16.5	16.7	16.4	13.0	6.38	1.37	6.79	13.5	18.1	21.7	26.6	30.7	27.8	24.6	20.3	14.8	6.79	1.39
100	15.5	15.4	15.3	14.9	11.5	5.13	1.49	6.28	11.1	14.2	15.8	18.1	20.8	18.9	17.3	15.0	11.4	6.15	1.57
105	15.7	15.4	15.0	13.7	10.1	3.63	1.70	5.58	10.3	12.6	13.5	14.4	15.5	14.6	13.9	12.7	10.3	5.54	1.82
110	17.0	16.3	15.4	13.1	8.70	2.64	1.95	4.34	9.54	11.7	12.4	12.9	13.2	12.8	12.4	11.7	9.43	4.46	2.10
115	20.1	18.2	15.4	12.6	7.33	2.48	2.22	3.40	8.78	11.2	11.9	12.2	12.3	12.1	11.9	11.1	8.77	3.72	2.38
120	25.1	21.9	16.5	11.9	6.01	2.65	2.49	3.01	8.02	11.0	11.8	12.1	12.0	11.9	11.7	10.8	8.05	3.44	2.63
125	31.0	27.5	17.9	11.4	5.10	2.87	2.75	3.14	7.92	11.1	12.2	12.4	12.3	12.2	12.0	10.8	7.70	3.61	2.89
130	35.2	32.1	20.7	12.4	4.01	3.08	3.00	3.32	7.67	12.4	13.5	13.6	13.6	13.5	13.0	11.5	7.55	3.79	3.13
135	34.6	32.4	25.0	11.4	3.67	3.32	3.24	3.30	5.82	15.8	17.1	17.1	17.0	16.6	15.7	14.2	7.05	3.65	3.37
140	31.3	29.0	17.7	5.81	3.72	3.55	3.48	3.37	6.05	14.3	23.4	24.0	23.5	23.2	21.5	14.6	8.38	3.56	3.60
145	15.3	13.0	7.14	3.95	3.84	3.78	3.73	3.61	6.41	9.28	19.9	28.1	29.8	27.9	21.5	12.4	8.78	3.76	3.82
150	5.81	5.06	4.23	4.11	4.06	4.01	3.96	3.86	5.18	10.0	12.1	18.1	22.2	20.1	15.9	13.3	6.42	3.98	4.04
155	4.40	4.41	4.34	4.30	4.27	4.22	4.18	4.10	4.18	8.50	12.2	13.3	15.9	16.1	14.8	9.95	4.47	4.19	4.24
160	4.54	4.53	4.50	4.47	4.45	4.41	4.37	4.31	4.25	5.40	9.11	12.0	13.3	12.0	9.38	5.73	4.31	4.38	4.42
165	4.69	4.67	4.65	4.63	4.61	4.58	4.55	4.50	4.46	4.41	5.15	6.91	7.01	5.92	4.85	4.45	4.49	4.55	4.59
170	4.80	4.78	4.78	4.76	4.75	4.72	4.70	4.67	4.64	4.60	4.57	4.55	4.55	4.55	4.59	4.63	4.66	4.70	4.73
175	4.88	4.86	4.86	4.85	4.84	4.82	4.82	4.80	4.79	4.77	4.75	4.74	4.74	4.73	4.76	4.79	4.80	4.81	4.83
180	4.89	4.86	4.88	4.88	4.88	4.88	4.89	4.89	4.89	4.88	4.87	4.89	4.89	4.87	4.88	4.89	4.88	4.88	4.89

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2020-12-29

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20
SPEC.: 高压灯带	DIM.: 1000*12*8	SERIAL No.: 20201229002
MFR.: EVERFINE	SUR.: 1000*12*8cm	Shielding Angle:

Table--2

UNIT: cd

C (DEG) □ (DEG)	285	300	315	330	345														
0	426	427	427	429	429														
5	422	421	419	419	419														
10	416	412	408	406	404														
15	405	399	392	389	385														
20	392	383	374	368	361														
25	376	364	352	342	335														
30	356	341	325	315	311														
35	333	315	297	290	283														
40	305	284	269	262	257														
45	272	251	239	241	244														
50	236	218	214	220	217														
55	198	185	183	178	169														
60	160	149	139	126	115														
65	122	109	95.9	87.4	81.9														
70	84.2	73.1	64.9	62.5	63.6														
75	52.8	46.4	43.8	45.6	48.0														
80	29.2	28.3	29.9	32.8	32.6														
85	13.5	18.5	22.3	23.6	23.9														
90	7.89	13.9	15.8	17.8	17.6														
95	4.51	12.1	15.1	15.6	15.5														
100	5.09	9.51	11.3	13.1	13.8														
105	3.68	9.75	12.1	12.6	13.3														
110	2.62	8.57	12.8	13.8	14.9														
115	2.50	6.69	12.6	15.7	17.5														
120	2.72	4.87	11.5	17.5	20.7														
125	2.96	3.87	10.8	20.9	27.4														
130	3.20	3.30	9.86	21.5	31.1														
135	3.43	3.49	5.30	17.5	31.3														
140	3.65	3.70	3.81	8.12	23.2														
145	3.87	3.90	3.99	4.09	6.72														
150	4.09	4.11	4.17	4.24	4.37														
155	4.29	4.31	4.35	4.38	4.47														
160	4.47	4.49	4.52	4.54	4.59														
165	4.63	4.65	4.67	4.68	4.73														
170	4.76	4.78	4.79	4.79	4.84														
175	4.85	4.86	4.86	4.86	4.90														
180	4.89	4.89	4.88	4.87	4.89														

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2020-12-29

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks: